

/ T-REX YELLOW**Structure**

Spiral PVC hose with double rigid shock-resistance PVC reinforcement. High resistance

Applications

Suction and delivery of liquids. Discharge and suction of tank cars or for uses at low temperatures. Industrial duty, agricultural use and for the passage of liquids. Heavy duty

Material

Suitable for passage of liquids in compliance with EU 10/2011 for simulants A, B and C. Phthalate free

Note

Double spiral patent, supersoft, high flexibility, long life

Struttura

Tubo spiralato in PVC con doppia spirale in PVC rigido antiurto. Alta resistenza

Applicazioni


Aspirazione e mandata liquidi. Spurghi e aspirazione di carri botte e per usi a basse temperature. Impieghi medi nel settore industriale, agricolo e per il passaggio dei liquidi alimentari. Impieghi gravosi

Materiali

Conforme alle direttive EU 10/2011 per il passaggio di liquidi alimentari per simulanti A, B e C. Esente da ftalati.

Note

Brevetto doppia spirale, supersoft, alta flessibilità, alta durabilità

**DOUBLE SPIRAL / SPIRALE DOPPIA**

Plasticised PVC / PVC plastificato

Rigid PVC spiral / Spirale in PVC rigido

Items not on stock, available up on request /
Articolo non a magazzino, disponibile su richiesta



Code / Codice	Ø internal / interno (mm)	Weight / Peso (gr)	Lenght / Lunghezza (m)	W.P. Bar	B.P. Bar	Radius	Vacuum (mH ² O)	€/m
TREXY20	20	350	50	11	33	110	9	
TREXY25	25	450	50	10	30	130	9	
TREXY30	30	520	50	9	27	150	9	
TREXY32	32	560	50	9	27	155	9	
TREXY35	35	600	50	9	27	165	9	
TREXY38	38	620	50	8	24	180	9	
TREXY40	40	700	50	7	21	195	9	
TREXY50	50	1000	50	7	21	235	9	
TREXY60	60	1200	50	6	18	275	9	
TREXY76	76	1700	50	5	15	340	9	
TREXY80	80	1800	50	4	12	365	9	
TREXY90	90	2200	30	4	12	420	9	
TREXY100	100	2700	30	3,5	10,5	470	9	
TREXY120	120	3500	30	2,5	7,5	650	9	
TREXY150	150	5000	20	1	3	780	9	